

L3 ANSWER 7 OF 10 JAPIO COPYRIGHT 1999 JPO and Japio  
AN 1991-192952 JAPIO  
TI FACSIMILE EQUIPMENT  
IN TAKAHASHI TOSHIHIKO  
PA NEC CORP, JP (CO 000423)  
PI JP03192952 A 19910822 Heisei  
AI JP1989-333503 (JP01333503 Heisei) 19891222  
SO PATENT ABSTRACTS OF JAPAN, Unexamined Applications, Section: E, Sect. No.  
1135, Vol. 15, No. 454, P. 6 (19911119)  
IC ICM (5) H04M011-00  
ICS (5) H04N001-32  
CC 44.4 COMMUNICATION - Telephone  
44.7 COMMUNICATION - Facsimile  
AB PURPOSE: To recognize the state at the end of communication even when the  
operator **leaves** the equipment after the operation of the  
transmission by calling a telephone set entirely independent of the  
**facsimile** equipment and **informing** the content of a  
**fault** in a voice from a voice synthesis section in the occurrence  
of a communication **fault**.  
CONSTITUTION: When an equipment control section 3 decides it that a  
communication end state signal is a signal representing a communication  
**fault**, the section 2 outputs a **fault** notice request  
signal 34 to a **fault** notice section 4 and the **fault**  
notice section 4 outputs a voice synthesized request signal 45 to a voice  
synthesis section 5. Moreover, the **fault** notice section 4  
outputs a readout request signal 41 of a telephone set 10 to a network  
control section 1 and makes dialing. When the telephone set 10 is called  
and a reply signal is detected, the **fault** notice voice signal 51  
synthesized by the voice synthesis section 5 is **informed** to the  
telephone set 10 via the network control section 1. Thus, even when the  
operator **leaves** the **facsimile** equipment 2 after the  
operator makes transmission from the **facsimile** equipment 2 to  
the **facsimile** equipment 1, the occurrence of communication  
**fault** is recognized.